



M26L - HALOSCAN MP SOFT 93035 DIM5



REFERENCE

23126 9035 B

AVAILABLE IN

BLACK 23126 9035 B

WHITE 23126 9035 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-35° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	35°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	478lm // 6,9W // 69lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

M26L - HALOSCAN MP SOFT 93035 DIM5

23126 9035 B

For detailed installation instructions, please consult the manual : [23126_XXX5_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

14


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

34

Dimtype: non-dimmable




21012 0230 LED POWER SUPPLY 48V-DC / 100W

14

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W

29


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



23110 0040 HALOSCAN LINEAR SPREAD LENS




23110 0050 B HALOSCAN HONEYCOMB B

DELTALIGHT

M26L - HALOSCAN MP SOFT 93035 DIM5

23126 9035 B



23110 0060 B HALOSCAN KAP MP B




23110 0060 W HALOSCAN KAP MP W




COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours



23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m




23375 0020 SLM35R - PROFILE 2m



M26L - HALOSCAN MP SOFT 93035 DIM5

23126 9035 B



23375 0030 SLM35R - PROFILE 3m



Notes: