



OML50 C - LED ARRAY UP TW 1968mm 950 DIM5

31147 9005



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 22,3W / CRI>90 (R9: 50) / 2700K-5000K / 2928lm Or @ 5000K: LED cluster 20,3W / CRI>90 (R9: 50) / 2700K-5000K / 3504lm
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	@ 2700K: 2928lm // 22,3W // 131lm/W Or @ 5000K: 3504lm // 20,3W // 173lm/W

Opties

WIRELESS CONTROL DIM5

Notes: