



OML50 C - LED ARRAY UP TW 1968mm 950 DIM5

31147 9005

 [View on website](#)



| General info | |
|------------------------------------|--|
| LOCATION | indoor |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 1 |
| INFORMATION | INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT |
| Electrical info | |
| ELECTRICAL | 220-240V / 0 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | DALI |
| ENERGY CLASS | E |
| CERTIFICATES | EPD, RCM |
| Lightsource info | |
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | @ 2700K: LED cluster 22,3W / CRI>90 (R9: 50) / 2700K-5000K / 2928lm Or @ 5000K: LED cluster 20,3W / CRI>90 (R9: 50) / 2700K-5000K / 3504lm |
| SDCM | SDCM3 |
| RISKGROUP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNICS (LIGHT SOURCE) | @ 2700K: 2928lm // 22,3W // 131lm/W Or @ 5000K: 3504lm // 20,3W // 173lm/W |

Options

WIRELESS CONTROL DIM5

Notes: