



OML50 - INFORM DU HE 984mm 24LED 94063 DIM5

31440 9435 B

BESCHIKBAAR IN
ZWART 31440 9435 B

 [Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.5
INFO	CLUSTER DOWN: 4029lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 24,5W / CRI>90 (R9: 50) / 4000K / 3965lm UP: LED cluster 12,2W / CRI>90 (R9: 50) / 4000K / 1982lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 3965lm // 24,5W // 162lm/W UP: 1982lm // 12,2W // 162lm/W

Opties

WIRELESS CONTROL DIM5

Notes: