
DELTALIGHT




OONO P70 927 DIM8

REFERENCE 29616 9208 N

AVAILABLE IN
BLACK 29616 9208 B
ANTHRACITE 29616 9208 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	3.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	572lm // 9,9W // 58lm/W

Options

PLATE 7
PIN 12
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : **29616_XXX8_HAND.pdf**


DELTALIGHT

OONO P70 927 DIM8

29616 9208 N

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

☐



216 12 01 IP68 CONNECTION KIT


☐



216 12 02 IP68 CONNECTOR 3P


☐

Pins and plates for bollards



229 01 12 PIN 12

☐



229 02 07 PLATE 7

☐

Notes: