






OONO P70 927 DIM8

29616 9208 N

AVAILABLE IN
BLACK 29616 9208 B
ANTHRACITE 29616 9208 N



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	3.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	572lm // 9,9W // 58lm/W

Options

PLATE 7
PIN 12
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual : [29616_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐

Cutout dimension (mm): 142 x 142




216 12 01 IP68 CONNECTION KIT

☐


216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 01 12 PIN 12

☐

229 02 07 PLATE 7

☐

Notes: