



LOGIC LINEAR 440 WALL GRAZER AG 940 DIM5

30825 9405 INOX

AVAILABLE IN
INOX 30825 9405 INOX



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	2.3
ADJUSTABILITY	non adjustable
INFORMATION	8 x WALLGRAZER LENS + ANTI GLARE SHIELD INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H07 RN-F 5 x 1mm ² 0,5m INCL.IP68 CONNECTOR 5P ESG 8mm max.500kg

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 64) / 4000K / 1949lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	1949lm // 14,4W // 131lm/W
LED TECHNICS (LUMINAIRE)	881lm // 16,6W // 53lm/W

Requirements

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : [30825_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




30810 0010 LOGIC LINEAR 440 BOX

☐

Cutout dimension (mm): 480 x 150

Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P

☐

Notes: