



## SOLI - 52 NLT 983020 Q-DIM



27119 732Q W

AVAILABLE IN

**BLACK** 27119 732Q B

**GOLD COLOURED** 27119 732Q GC

**WHITE** 27119 732Q W



[View on website](#)



### General info

|                           |                                                                                                                                |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                         |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                                                                                 |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                           |
| <b>WEIGHT (KG)</b>        | 0.4                                                                                                                            |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 360° rotatable                                                                                            |
| <b>INFORMATION</b>        | REFLECTOR FL-20°<br>EXCL. LED POWER SUPPLY 48V-DC<br>NLT = Natural Light Technology<br>Optional REFLECTORS 30° & 45° available |

### Electrical info

|                     |               |
|---------------------|---------------|
| <b>ELECTRICAL</b>   | 48V-DC        |
| <b>CLASS</b>        | III           |
| <b>DIM TYPE</b>     | Qbus dim      |
| <b>ENERGY CLASS</b> | F             |
| <b>CERTIFICATES</b> | CB, ENEC, LCA |

### Lightsource info

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                |
| <b>LIGHTSOURCE</b>                 | LED array 10,7W / CRI>98 (R9: 98) / 3000K / 1040lm |
| <b>TM-30 VALUES</b>                | rf: 98 / Rg: 101                                   |
| <b>SDCM</b>                        | SDCM2                                              |
| <b>RISKGROUP</b>                   | RG1                                                |
| <b>LM80</b>                        | L90B10 > 50000                                     |
| <b>BEAMANGLE</b>                   | 20°                                                |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1040lm // 10,7W // 97lm/W                          |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 652lm // 12,3W // 53lm/W                           |

### Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

### Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42

SOFTENING LENS 42

GLASS SBL 42

For detailed installation instructions, please consult the manual : [27119\\_XXXQ\\_HAND.pdf](#)


FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                          |    | # of Fixtures             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------|
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |    | Min current   Max current |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>5510090</div></div></div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>300 89 48 100</div><div>LED POWER SUPPLY 48V-DC / 100W DIN</div></div><div>Dimtype: non-dimmable</div></div>                              | 9  | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>63114125</div></div></div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>300 89 48 240</div><div>LED POWER SUPPLY 48V-DC / 240W DIN</div></div><div>Dimtype: non-dimmable</div></div>                             | 23 | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>1729830</div></div></div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>21012 0230</div><div>LED POWER SUPPLY 48V-DC / 100W</div></div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div> | 9  | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>2239230</div></div></div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>21012 0240</div><div>LED POWER SUPPLY 48V-DC / 200W</div></div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div> | 19 | <div></div>               |
| Light altering devices                                                                                                                                                                                                                                                                                                                                      |    |                           |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>13</div></div></div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>19810 0010 B</div><div>HONEYCOMB 42 SINGLE USE B</div></div></div>                                                                             |    | <div></div>               |
| <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>13</div></div></div> <div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>19810 0020</div><div>LINEAR SPREAD LENS 42</div></div></div>                                                                                   |    | <div></div>               |

# DELTALIGHT

## SOLI - 52 NLT 983020 Q-DIM


27119 732Q W




**19810 0030** SPREAD LENS 42

☐

**19810 0040** SOFTENING LENS 42

☐


**19810 0050** GLASS SBL 42

☐

**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

☐

### Finish your product



**19810 0100 B** SPY 52 TUBE B

☐

**19810 0100 FBR** SPY 52 TUBE FBR

☐

**19810 0100 FG** SPY 52 TUBE FG

☐


**19810 0100 GC** SPY 52 TUBE GC

☐

**19810 0100 W** SPY 52 TUBE W

☐

### Replaceable reflector / lens



**19810 0180** SPY 52 REFLECTOR 20°

☐

# DELTALIGHT

## SOLI - 52 NLT 983020 Q-DIM

27119 732Q W



**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°




### COMPATIBLE COMPOSABLES

#### SOLISCAPE profile

#### Available Colours



**27111 0020** SOLI - PROFILE 2m



**27111 0030** SOLI - PROFILE 3m



Notes: