





M20/M26H - NEEDLE OK 92733 MDL

25018 9220 FG

AVAILABLE IN

BLACK BRONZE 25018 9220 BBR

FLEMISH GOLD 25018 9220 FG



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 50° swiveling, 350° rotatable
INFORMATION	LENS FL-33° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,7W / CRI>90 (R9: 56) / 2700K / 519lm
TM-30 VALUES	rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUPE	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	519lm // 5,7W // 90lm/W
LED TECHNICS (LUMINAIRE)	380lm // 6,6W // 58lm/W

Remarks
Take a look at our MAGNETIC PROFILES movie

Requirements
LED POWER SUPPLY 48V-DC

Options
DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [25018_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

29

Dimtype: WDL = wireless dimmable


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

29

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

29

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

15

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN



36

Dimtype: non-dimmable





DELTALIGHT

M20/M26H - NEEDLE OK 92733 MDL

25018 9220 FG

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	15 ☐
	Dimtype: non-dimmable	
	Cutout dimension (mm): 40	
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	30 ☐
	Dimtype: non-dimmable	
	Cutout dimension (mm): 40	

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile	Available Colours
 23359 0000 SLM26H - PROFILE	 
 23359 0010 SLM26H - PROFILE 1m	 
 23359 0020 SLM26H - PROFILE 2m	         
 23359 0030 SLM26H - PROFILE 3m	         
SPLITLINE M20 ST profile	Available Colours
 23397 0000 SPM20 ST - PROFILE	 
 23397 0020 SPM20 ST - PROFILE 2m	 
 23397 0030 SPM20 ST - PROFILE 3m	 

DELTALIGHT

M20/M26H - NEEDLE OK 92733 MDL

25018 9220 FG

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: