



OML50 - INFORM DU HE 1312mm 8+8LED 93063

31441 9330 B

BESCHIKBAAR IN
ZWART 31441 9330 B



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.2
INFO	CLUSTER DOWN: 1932lm/m CLUSTER UP: 1932lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 2534lm // 16,3W // 155lm/W UP: 2534lm // 16,3W // 155lm/W

Notes: