





D-LINER 19 SBL LOC1 1020 940
DIM5

32038 9405 B

AVAILABLE IN
BLACK 32038 9405 B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE 5 x 0,75mm ² - 0,5m + WIELAND PLUG GST18i5 male pastelblue
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 25W / CRI>90 (R9: 59) / 4000K / 2600lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	2600lm // 25W // 1m/W
LED TECHNICS (LUMINAIRE)	1950lm // 28,8W // 68lm/W

For detailed installation instructions, please consult the manual : [32038_XXX5_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-

D-LINER 19 SBL LOC1 1020 940 DIM5

32038 9405 B



Acoustic climate-control ceiling Hunter Douglas 30BD

Notes: