
DELTALIGHT




M20/M26H - NEEDLE OK 93013 MDL

REFERENCE 25018 9310 FG

AVAILABLE IN
BLACK BRONZE 25018 9310 BBR
FLEMISH GOLD 25018 9310 FG





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 50° swiveling, 350° rotatable
INFORMATION	LENS SP-13° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	G
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,7W / CRI>90 (R9: 55) / 3000K / 519lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	13°
LED TECHNICS (LIGHT SOURCE)	519lm // 5,7W // 90lm/W
LED TECHNICS (LUMINAIRE)	364lm // 6,6W // 56lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **25018_XXX0_HAND.pdf**

M20/M26H - NEEDLE OK 93013 MDL

25018 9310 FG


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 29


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 29

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 29


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 15

Dimtype: non-dimmable




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 36

Dimtype: non-dimmable

M20/M26H - NEEDLE OK 93013 MDL


25018 9310 FG



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 15

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 30

Dimtype: non-dimmable


Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES


SHIFTLINE M26H profile — Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m







23397 0030 SPM20 ST - PROFILE 3m

DELTALIGHT

M20/M26H - NEEDLE OK 93013 MDL

25018 9310 FG

SPLITLINE M20 profile	Available Colours
 **420 20 10 00** SPM20 - PROFILE 1m	
 **420 20 20 00** SPM20 - PROFILE 2m	
 **420 20 30 00** SPM20 - PROFILE 3m	
 **23301 0000** SPM20 - PROFILE B	

Notes: