





M26L - SPY 52 TW 96530 DIM5

23215 9045 B

AVAILABLE IN
BLACK 23215 9045 B
WHITE 23215 9045 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC DALI DT8 dimming Optional REFLECTORS 20° & 45° available
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	694lm // 10,4W // 67lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 52 TUBE
 LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42
 SPREAD LENS 42
 LINEAR SPREAD LENS 42
 SOFTENING LENS 42
 GLASS SBL 42

For detailed installation instructions, please consult the manual : [23215_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	9	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	23	
1729830 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	9	
2239230 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	19	
Light altering devices		
13Ø42 19810 0010 B HONEYCOMB 42 SINGLE USE B		
13Ø42 19810 0020 LINEAR SPREAD LENS 42		

DELTALIGHT

M26L - SPY 52 TW 96530 DIM5

23215 9045 B



19810 0030 SPREAD LENS 42

☐

19810 0040 SOFTENING LENS 42

☐

19810 0050 GLASS SBL 42

☐

19810 0060 B HONEYCOMB 42 DOUBLE USE B

☐

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

19810 0100 FG SPY 52 TUBE FG

☐

19810 0100 GC SPY 52 TUBE GC

☐

19810 0100 W SPY 52 TUBE W

☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

DELTALIGHT

M26L - SPY 52 TW 96530 DIM5

23215 9045 B



19810 0190 SPY 52 REFLECTOR 45°




19810 0240 SPY 52 REFLECTOR 30°




COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile

Available Colours



23375 0000 SLM35R - PROFILE




23375 0010 SLM35R - PROFILE 1m




DELTALIGHT

M26L - SPY 52 TW 96530 DIM5

23215 9045 B



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m



Notes: