





SUPERNOVA FLAT 95 930

20635 9300 B

AVAILABLE IN

NOIR 20635 9300 B

BLANC 20635 9300 W



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Applique,Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	15.1
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL INCLADJUSTABLE LED POWER SUPPLY - 3 settings: 1- 2800mA 2- 1860mA 3- 1300mA
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non dimmable
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2800: LED cluster 123,7W / CRI>90 (R9: 68) / 3000K / 16507lm Or @ 1860: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm Or @ 1300: LED cluster 54,2W / CRI>90 (R9: 68) / 3000K / 8273lm
RVALUES	Rf: 89 / Rg: 97 @ 1860: rf: 89 / Rg: 97 @ 1300: rf: 89 / Rg: 97
SDMC	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2800: 16507lm // 123,7W // 133lm/W Or @ 1860: 11477lm // 79,4W // 144lm/W Or @ 1300: 8273lm // 54,2W // 153lm/W
LED TECHNICS (LUMINAIRE)	@ 2800: 12659lm // 142,3W // 89lm/W Or @ 1860: 8802lm // 91,3W // 96lm/W Or @ 1300: 6345lm // 62,3W // 102lm/W

DELTALIGHT

SUPERNOVA FLAT 95 930

20635 9300 B


Options

- SUSPENSION SET 25 3m
- CABLE BASE R / S
- COVERSET R 62-90-100 / S 62-80-90
- CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
- CENTRAL SUSPENSION SUPERNOVA FLAT


For detailed installation instructions, please consult the manual : [20635_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation

	41 203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	41 203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐






les sets pour recouvrement plafond

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐

DELTALIGHT

SUPERNOVA FLAT 95 930

20635 9300 B


	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 95 930

20635 9300 B


les accessoires de suspension




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

☐

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W

☐

328 25 43 SUSPENSION SET 25 3m

☐

328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

☐

les accessoires pour connexions électriques



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: