





LOGIC LINEAR 880 WALL GRAZER AG 940

REFERENCE

30826 9400 INOX

AVAILABLE IN

INOX 30826 9400 INOX



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	4.4
ADJUSTABILITY	non adjustable
INFORMATION	16 x WALLGRAZER LENS + ANTI GLARE SHIELD INCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H05 RN-F 3 x 0.75mm ² 0,5m INCL.IP68 CONNECTOR 3P ESG 8mm max.500kg

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 64) / 4000K / 3898lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	3898lm // 28,8W // 131lm/W
LED TECHNICS (LUMINAIRE)	1763lm // 33,1W // 53lm/W

Requirements

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : [30826_XXX0_HAND.pdf](#)


DELTA LIGHT

LOGIC LINEAR 880 WALL GRAZER AG 940

30826 9400 INOX

FINISH YOUR SPECIFICATION

Ground mounting boxes




30810 0030

LOGIC LINEAR 880 BOX

☐

Cutout dimension (mm): 920 x 150


Waterproof connection parts



431 99 02

IP68 JUNCTION BOX 4P

☐



21034 0150

IP68 Y-CONNECTOR 5P

☐

Notes: