





PARTOU AC 92733 DIM8

REFERENCE 25217 9228 W

AVAILABLE IN
BLACK 25217 9228 B
FLEMISH BRONZE 25217 9228 FBR
FLEMISH GOLD 25217 9228 FG
WHITE 25217 9228 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33°
Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	G
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	597lm // 8W // 75lm/W
LED TECHNICS (LUMINAIRE)	504lm // 8W // 63lm/W
Options	
PLASTERKIT 101	

For detailed installation instructions, please consult the manual : [25217_XXX8_HAND.pdf](#)

DELTALIGHT

PARTOU AC 92733 DIM8


25217 9228 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	 202 11 19 - PLASTERKIT 101 Required
 Wood	-
 Concrete + plaster	 202 11 19 - PLASTERKIT 101 Required
 Lintel + plaster	 202 11 19 - PLASTERKIT 101 Required
 Hollow-core slab + plaster	 202 11 19 - PLASTERKIT 101 Required
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Plasterkits



202 11 19 PLASTERKIT 101



Cutout dimension (mm): 80 x 180

Notes: