




SPYCO CLIP AC 92733 DIM8

REFERENCE 19918 9228 B

AVAILABLE IN
BLACK 19918 9228 B
WHITE 19918 9228 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-33° BLACK version: INCL.SPY TUBE S B / WHITE version: INCL.SPY TUBE S W
Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	G
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	597lm // 8W // 75lm/W
LED TECHNICS (LUMINAIRE)	452lm // 8W // 57lm/W
Accessories	
SPY TUBE S	

For detailed installation instructions, please consult the manual : [19918_XXX8_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Hollow-core slab	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Finish your product

	414 02 00 B	SPY TUBE S B	☐
	414 02 00 FBR	SPY TUBE S FBR	☐
	414 02 00 FG	SPY TUBE S FG	☐
	414 02 00 MMAT	SPY TUBE S MMAT	☐
	414 02 00 SG	SPY TUBE S SG	☐
	414 02 00 W	SPY TUBE S W	☐

DELTALIGHT

SPYCO CLIP AC 92733 DIM8

19918 9228 B

Notes: