



SPY 52 ON SOFT 93045

19899 9030 FG

AVAILABLE IN

NOIR 19899 9030 B


FLEMISH BRONZE 19899 9030 FBR

FLEMISH GOLD 19899 9030 FG

ENTIÈREMENT BLANC 19899 9030 FW

COULEUR OR 19899 9030 GC

BLANC 19899 9030 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	REFLECTOR WFL-45° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC Optional REFLECTORS 20° & 30° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	664lm // 11,7W // 57lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 500mA-DC DIM

Options








COVERSET R 90-100

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual : [19899_XXX0_HAND.pdf](#)










FINISH YOUR SPECIFICATION

les alimentations led			# of Fixtures
web2print_power_supply_info_box			Min current Max current
	300 48 500 ED1	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	2 ☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 30		
	300 48 500 ED5	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2 ☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 500 MDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	2 ☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 30		
	300 48 500 WDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	2 ☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 45		
	300 90 61	LED POWER SUPPLY MULTI-POWER DIM6	2 ☐
	Dimtype: fin de phase ou bouton poussoir		
	Cutout dimension (mm): 56		
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	3(3) ☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	Cutout dimension (mm): 82		
	300 90 64	LED POWER SUPPLY MULTI-POWER DIM7	2(1) ☐
	Dimtype: 1 à 10 V ou bouton poussoir		
	Cutout dimension (mm): 72		

DELTALIGHT

SPY 52 ON SOFT 93045




19899 9030 FG

	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5	2(1) ☐
	Dimtype: DALI	
	Cutout dimension (mm): 72	
	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9	5(3) ☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir	
	Cutout dimension (mm): 84	
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7	1(1) ☐
	Dimtype: 1 à 10 V ou bouton poussoir	
	Cutout dimension (mm): 55	
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) ☐
	Dimtype: DALI	
	Cutout dimension (mm): 55	
	<u>21012 0010</u> LED POWER SUPPLY MULTI POWER	2 ☐
	Dimtype: non dimmable	
	Cutout dimension (mm): 50	
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	2 ☐
	Dimtype: 1 à 10 V	
	Cutout dimension (mm): 54	
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	2 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 54	
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	3(3) ☐
	Dimtype: WDL = dimmable sans fil	
	Cutout dimension (mm): 84	
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	2 ☐
	Dimtype: WDL = dimmable sans fil	
	Cutout dimension (mm): 54	
	<u>21012 0278</u> LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 ☐
	Dimtype: fin de phase	
	Cutout dimension (mm): 55	



DELTALIGHT

SPY 52 ON SOFT 93045


19899 9030 FG

	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐
Dimtype: fin de phase			
Cutout dimension (mm): 55			
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1	☐
Dimtype: fin de phase			
Cutout dimension (mm): 48			
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2	☐
Dimtype: DALI			
Cutout dimension (mm): 30			

les sets pour recouvrement plafond

	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐
	204 00 100 ANO COVERSET R 100 ANO	☐
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐





modifier les dispositifs de lumière

	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
--	---	--------------------------

DELTALIGHT

SPY 52 ON SOFT 93045

19899 9030 FG

	19810 0020	LINEAR SPREAD LENS 42	☐
	19810 0030	SPREAD LENS 42	☐
	19810 0040	SOFTENING LENS 42	☐
	19810 0050	GLASS SBL 42	☐
	19810 0060 B	HONEYCOMB 42 DOUBLE USE B	☐

Terminez votre produit


	19810 0100 B	SPY 52 TUBE B	☐
	19810 0100 FBR	SPY 52 TUBE FBR	☐
	19810 0100 FG	SPY 52 TUBE FG	☐
	19810 0100 GC	SPY 52 TUBE GC	☐
	19810 0100 W	SPY 52 TUBE W	☐

DELTALIGHT


SPY 52 ON SOFT 93045

19899 9030 FG


Réflecteur / lentille remplaçable



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: