DELTALIGHT

KIX II PIN 24V 93055

REFERENCE 13531 9330 N

AVAILABLE IN
ALU GREY 13531 9330 A
ANTHRACITE 13531 9330 N
PINE GREEN 13531 9330 PGR





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.2
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-55° INCL.1 x CABLE H05 RN-F 2 x 1mm² 2m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output)

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	55°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	646lm // 6,7W // 97lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

Accessories

KAP KIX
HONEYCOMB KIX

DELTALIGHT

KIX II PIN 24V 93055

13531 9330 N

For detailed installation instructions, please consult the manual : **13531_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W — 21

Dimtype: non-dimmable

Cutout dimension (mm): 75



21012 0160 LED POWER SUPPLY 24V-DC / 24W — 3

Dimtype: non-dimmable

Cutout dimension (mm): 55



21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 — 8

Dimtype: 1-10V

Cutout dimension (mm): 61



21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 — 12

Dimtype: 1-10V

Cutout dimension (mm): 70



21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 — 17

Dimtype: 1-10V

Cutout dimension (mm): 70

Miscellaneous control equipment



21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)

DELTALIGHT

KIX II PIN 24V 93055

13531 9330 N

Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142



216 12 01 IP68 CONNECTION KIT

216 12 02 IP68 CONNECTOR 3P

Light altering devices



232 10 00 N KAP KIX N



232 10 03 N HONEYCOMB KIX N

Notes: