

OML50 - LED ARRAY D TW
CORNER V90° 950 DIM5

31064 9005

 [View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: 2 x (LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm) Or @ 5000K: 2 x (LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm)
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W

Options
WIRELESS CONTROL DIM5

Notes: