





## SPY 52 93020 ADM SLIM DIM5

19836 9325 W

AVAILABLE IN  
**BLACK** 19836 9325 B  
**WHITE** 19836 9325 W



[View on website](#)



| General info                |                                                                                                                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                                                                                                                             |
| INSTALLATION                | Mains voltage track Mains voltage track mounted                                                                                                                                                    |
| INGRESS PROTECTION          | IP20                                                                                                                                                                                               |
| WEIGHT (KG)                 | 0.4                                                                                                                                                                                                |
| ADJUSTABILITY               | 0° to 90° swiveling, 360° rotatable                                                                                                                                                                |
| INFORMATION                 | REFLECTOR FL-20°<br>3F MULTI DIMMABLE POWER SLIM ADAPTER 350-700mA<br>Current selection via jumper on adapter<br>Optional REFLECTORS 30° & 45° available                                           |
| Electrical info             |                                                                                                                                                                                                    |
| ELECTRICAL                  | 220-240V / 50-60Hz                                                                                                                                                                                 |
| CLASS                       | II                                                                                                                                                                                                 |
| POWER SUPPLY                | YES                                                                                                                                                                                                |
| DIM TYPE                    | DALI                                                                                                                                                                                               |
| ENERGY CLASS                | D                                                                                                                                                                                                  |
| CERTIFICATES                | CB, RCM                                                                                                                                                                                            |
| Lightsource info            |                                                                                                                                                                                                    |
| LIGHTSOURCE NAME            | LED                                                                                                                                                                                                |
| LIGHTSOURCE                 | @ 700mA: LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm<br>Or<br>@ 500mA: LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm<br>Or<br>@ 350mA: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| TM-30 VALUES                | @ 700mA: rf: 90 / Rg: 99<br>@ 500mA: rf: 90 / Rg: 99<br>@ 350mA: rf: 90 / Rg: 99                                                                                                                   |
| SDCM                        | SDCM1                                                                                                                                                                                              |
| RISKGROUP                   | RG1                                                                                                                                                                                                |
| LM80                        | L90B10 > 50000                                                                                                                                                                                     |
| BEAMANGLE                   | 20°                                                                                                                                                                                                |
| LED TECHNICS (LIGHT SOURCE) | @ 700mA: 1467lm // 12,4W // 118lm/W<br>Or<br>@ 500mA: 1089lm // 8,6W // 127lm/W<br>Or<br>@ 350mA: 787lm // 5,8W // 135lm/W                                                                         |
| LED TECHNICS (LUMINAIRE)    | @ 700mA: 919lm // 14,3W // 64lm/W<br>Or<br>@ 500mA: 682lm // 9,9W // 69lm/W<br>Or<br>@ 350mA: 493lm // 6,7W // 74lm/W                                                                              |

## SPY 52 93020 ADM SLIM DIM5

19836 9325 W

### Requirements

SPY 52 TUBE  
TRACK 3F DIM






### Accessories

HONEYCOMB 42  
SPREAD LENS 42  
LINEAR SPREAD LENS 42  
SOFTENING LENS 42  
GLASS SBL 42

For detailed installation instructions, please consult the manual : [19836\\_XXX5\\_HAND.pdf](#)

## FINISH YOUR SPECIFICATION

### Light altering devices

|                                                                                    |                                               |                          |
|------------------------------------------------------------------------------------|-----------------------------------------------|--------------------------|
|  | <b>19810 0010 B</b> HONEYCOMB 42 SINGLE USE B | <input type="checkbox"/> |
|  | <b>19810 0020</b> LINEAR SPREAD LENS 42       | <input type="checkbox"/> |
|  | <b>19810 0030</b> SPREAD LENS 42              | <input type="checkbox"/> |
|  | <b>19810 0040</b> SOFTENING LENS 42           | <input type="checkbox"/> |
|  | <b>19810 0050</b> GLASS SBL 42                | <input type="checkbox"/> |
|  | <b>19810 0060 B</b> HONEYCOMB 42 DOUBLE USE B | <input type="checkbox"/> |

# DELTALIGHT

## SPY 52 93020 ADM SLIM DIM5

19836 9325 W

### Finish your product

|                                                                                  |                                       |                          |
|----------------------------------------------------------------------------------|---------------------------------------|--------------------------|
|  | <b>19810 0100 B</b> SPY 52 TUBE B     | <input type="checkbox"/> |
|                                                                                  | <b>19810 0100 FBR</b> SPY 52 TUBE FBR | <input type="checkbox"/> |
|                                                                                  | <b>19810 0100 FG</b> SPY 52 TUBE FG   | <input type="checkbox"/> |
|                                                                                  | <b>19810 0100 GC</b> SPY 52 TUBE GC   | <input type="checkbox"/> |
|                                                                                  | <b>19810 0100 W</b> SPY 52 TUBE W     | <input type="checkbox"/> |

### Replaceable reflector / lens

|                                                                                    |                                        |                          |
|------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
|  | <b>19810 0180</b> SPY 52 REFLECTOR 20° | <input type="checkbox"/> |
|  | <b>19810 0190</b> SPY 52 REFLECTOR 45° | <input type="checkbox"/> |
|  | <b>19810 0240</b> SPY 52 REFLECTOR 30° | <input type="checkbox"/> |

## COMPATIBLE TRACKS

| TRACK 3F DIM H    |                    |               | Available Colours                                                                     |                                                                                       |
|-------------------|--------------------|---------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>200 14 410</b> | TRACK 3F DIM H 1m  | 1000 m 1.6 kg |  |  |
| <b>200 14 420</b> | TRACK 3F DIM H 2m  | 2000 m 3.2 kg |  |  |
| <b>200 14 430</b> | TRACK 3F DIM H 3m  | 3000 m 4.8 kg |  |  |
| TRACK 3F DIM IN   |                    |               | Available Colours                                                                     |                                                                                       |
| <b>200 13 410</b> | TRACK 3F DIM IN 1m | 1000 m 1.2 kg |  |  |

# DELTALIGHT

## SPY 52 93020 ADM SLIM DIM5

19836 9325 W

|                                      |        |                          |                                                                                                                                                                                                                                                             |
|--------------------------------------|--------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>200 13 420</b> TRACK 3F DIM IN 2m | 2000 m | 2.4 kg                   |                                                                                       |
| <b>200 13 430</b> TRACK 3F DIM IN 3m | 3000 m | 3.5 kg                   |                                                                                       |
| <b>TRACK 3F DIM ON</b>               |        | <b>Available Colours</b> |                                                                                                                                                                                                                                                             |
| <b>200 12 410</b> TRACK 3F DIM ON 1m | 1000 m | 1.1 kg                   |    |
| <b>200 12 420</b> TRACK 3F DIM ON 2m | 2000 m | 2.1 kg                   |    |
| <b>200 12 430</b> TRACK 3F DIM ON 3m | 3000 m | 3.1 kg                   |    |

Notes: