



M26L - SPY 391 SOFT 93040 DIM5

23438 9035 BRAT

AVAILABLE IN

NEGRO 23438 9035 B

ALU CEPILLADO 23438 9035 BRA

ANTRACITA CEPILLADO 23438 9035 BRAT

COBRE CEPILLADO 23438 9035 BRCU

ORO CEPILLADO 23438 9035 BRG

BRONCE VIEJO CEPILLADO 23438 9035 BROB



FLEMISH BRONZE 23438 9035 FBR

FLEMISH GOLD 23438 9035 FG

ORO COLOREADO 23438 9035 GC

NEGRO PIANO 23438 9035 PB

BLANCO 23438 9035 W



[View on website](#)



General info	
LOCATION	interior
INSTALLATION	Sistemas de baja tensión Montado en sistemas de baja tensión
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° giratorio, 360° orientable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	con DALI
ENERGY CLASS	F
CERTIFICATES	EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W
Requirements	
SPY 39 TUBE	
LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : [23438_XXX5_HAND.pdf](#)

M26L - SPY 391 SOFT 93040 DIM5

23438 9035 BRAT

FINISH YOUR SPECIFICATION

Fuente de Alimentación LED

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: no dimerizable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: no dimerizable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: no dimerizable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

17

Dimtype: no dimerizable

Cutout dimension (mm): 40

Termina tu producto



24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR

24144 0010 FG SPY 39 TUBE FG

24144 0010 GC SPY 39 TUBE GC

24144 0010 W SPY 39 TUBE W

DELTALIGHT

M26L - SPY 391 SOFT 93040 DIM5





23438 9035 BRAT



24144 0070 SPY 39 TUBE SBL



COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 23358 0000 SLM26L - PROFILE	 
 23358 0010 SLM26L - PROFILE 1m	 
 23358 0020 SLM26L - PROFILE 2m	         
 23358 0030 SLM26L - PROFILE 3m	         

Notes: