


27933 9005 W

Technical drawing of a circular flange. The outer diameter is $\varnothing 300$. The inner diameter is $\varnothing 100$. The thickness of the flange is 47. The central hole has a diameter of 32 and a depth of 259.

 [Voir sur le site Web](#)

Info Source lumineuse	
LIGHTSOURCE NAME	LED
SOURCE DE LUMIÈRE	@ 2700K: LED cluster 9,4W / CRI>90 (R9: 63) / 2700K-6500K / 1338lm Or @ 6500K: LED cluster 9,4W / CRI>90 (R9: 81) / 2700K-6500K / 1428lm
SDCM	SDCM3
GROUPE DE RISQUE	RG0
LM80	L70 > 60000
TECHNIQUES LED (SOURCE LUMINEUSE)	@ 2700K: 1338lm // 9,4W // 142lm/W Or @ 6500K: 1428lm // 9,4W // 152lm/W
TECHNIQUES LED (LUMINAIRE)	@ 2700K: 993lm // 10,8W // 92lm/W Or @ 6500K: 1059lm // 10,8W // 98lm/W

Références obligatoires

Delta Light NV may revise the information and technical data at any time without notice. Version: 26/08/2026

TRACKS COMPATIBLES

TRACK 3F DIM H			Couleurs disponibles	
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg		
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg		
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg		
TRACK 3F DIM IN			Couleurs disponibles	
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg		
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg		
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg		
TRACK 3F DIM ON			Couleurs disponibles	
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg		
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg		
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg		

Notes: