



## M20/M26H - NEEDLE OK 93013 DIM5



### REFERENCE

25019 9315 BBR

### AVAILABLE IN

**BLACK BRONZE** 25019 9315 BBR

**FLEMISH GOLD** 25019 9315 FG



[View on website](#)



### General info

|                           |                                                |
|---------------------------|------------------------------------------------|
| <b>LOCATION</b>           | indoor                                         |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted |
| <b>INGRESS PROTECTION</b> | IP20                                           |
| <b>WEIGHT (KG)</b>        | 0.3                                            |
| <b>ADJUSTABILITY</b>      | 0° to 50° swiveling, 350° rotatable            |
| <b>INFORMATION</b>        | LENS SP-13°<br>EXCL.LED POWER SUPPLY 48V-DC    |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | G        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                              |
| <b>LIGHTSOURCE</b>                 | LED array 5,7W / CRI>90 (R9: 55) / 3000K / 519lm |
| <b>TM-30 VALUES</b>                | Rf: 92 / Rg: 98                                  |
| <b>SDCM</b>                        | SDCM2                                            |
| <b>RISKGROUPE</b>                  | RG2 (threshold 0,6m)                             |
| <b>LM80</b>                        | L90B10 > 41000                                   |
| <b>BEAMANGLE</b>                   | 13°                                              |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 519lm // 5,7W // 90lm/W                          |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 364lm // 6,6W // 56lm/W                          |

### Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

### Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [25019\\_XXX5\\_HAND.pdf](#)

## M20/M26H - NEEDLE OK 93013 DIM5

25019 9315 BBR

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

15


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

36

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

15

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

30

Dimtype: non-dimmable

Cutout dimension (mm): 40

### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26H + SBL

#### Available Colours



**30411 9205** SHIFTLINE M26H + SBL 2m DIM5



**30411 9305** SHIFTLINE M26H + SBL 2m DIM5




**30412 9205** SHIFTLINE M26H + SBL 3m DIM5




# DELTALIGHT

## M20/M26H - NEEDLE OK 93013 DIM5


25019 9315 BBR



**30412 9305** SHIFTLINE M26H + SBL 3m DIM5



**30413 9205** SHIFTLINE M26H + SBL 4m DIM5




**30413 9305** SHIFTLINE M26H + SBL 4m DIM5




### SHIFTLINE M26H profile


### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

### Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m



# DELTALIGHT

## M20/M26H - NEEDLE OK 93013 DIM5

25019 9315 BBR




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: