





SPLIT-IT SPY 66 93018

18434 9310 W

AVAILABLE IN
BLACK 18434 9310 B
WHITE 18434 9310 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
INFORMATION	ADJUSTABLE REFLECTOR SP-18° EXCLLED POWER SUPPLY 48V-DC EXCLLED POWER CONVERTER 48V TO 500mA-DC PRO Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-17,2W / CRI>90 (R9: 52) / 3000K / 1524-2101lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	2101lm // 17,2W // 123lm/W
LED TECHNICS (LUMINAIRE)	1500lm // 19,8W // 76lm/W

Requirements

SPY 66 TUBE
 LED POWER CONVERTER 48V-DC to 500 mA-DC
 LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING 48V-DC


Accessories

HONEYCOMB 57
 SPREAD LENS 57
 LINEAR SPREAD LENS 57
 SOFTENING LENS 57
 GLASS SBL 57

For detailed installation instructions, please consult the manual : [18434_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



416 99 00 THROUGH WIRING 48V-DC SPLIT-IT PRO


☐

LED power supplies

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 500 PRO ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM1

1 ☐

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 500 PRO ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM5

1 ☐

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 PRO WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO WDL

1 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

1|1 ☐

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9











2(2) | 2(2) ☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82

SPLIT-IT SPY 66 93018









18434 9310 W

	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	1(1) 1(0)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	1 -	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(1) 1(0)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	3(3) 3(2)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	1(1) 1(0)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) 1(0)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	2->2 2	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1 1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 1	☐


DELTALIGHT

SPLIT-IT SPY 66 93018

18434 9310 W

	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	2(2) 2(2)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1 1	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	1	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	1 1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	1(1)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	1(0)	☐
	21032 0375 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W PRO DIM5 Dimtype: DALI Cutout dimension (mm): 30	1	☐


Light altering devices

	24611 0150 B HONEYCOMB 57 SINGLE USE B		☐
--	---	--	--------------------------

DELTALIGHT


SPLIT-IT SPY 66 93018

18434 9310 W




¹³ **24611 0160** GLASS SBL 57

☐




¹⁵ **24611 0170** LINEAR SPREAD LENS 57

☐




¹³ **24611 0190** SOFTENING LENS 57

☐



¹⁴ **24611 0200** SPREAD LENS 57

☐



¹⁴ **24611 0210 B** HONEYCOMB 57 DOUBLE USE B

☐

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

DELTALIGHT

SPLIT-IT SPY 66 93018

18434 9310 W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

COMPATIBLE COMPOSABLES

SPLIT-IT PRO profile

Available Colours



372 01 00 SPT PRO - PROFILE



Notes: