



SPLITBOX 3 SPY 52 SOFT 93045

100075 9030 W

AVAILABLE IN
BLACK 100075 9030 B
WHITE 100075 9030 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 365 x 150
RECESSED DEPTH (MM)	180
THICKNESS OF MOUNTING SURFACE (MM)	max.12
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.8
INFORMATION	ADJUSTABLE 3 x REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC Optional REFLECTORS 20° & 30° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm)
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	3114lm // 30,6W // 109lm/W
LED TECHNICS (LUMINAIRE)	1992lm // 35,2W // 57lm/W

Requirements	
SPY 52 TUBE	
LED POWER SUPPLY 500mA-DC DIM	

Accessories	
HONEYCOMB 42	
SPREAD LENS 42	
LINEAR SPREAD LENS 42	
SOFTENING LENS 42	
GLASS SBL 42	

For detailed installation instructions, please consult the manual : [100075_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-




FINISH YOUR SPECIFICATION

LED power supplies


of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1(1)
Dimtype: 1-10V or DALI or push button		
Cutout dimension (mm): 82		
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	1(1)
Dimtype: 1-10V or DALI or push button		
Cutout dimension (mm): 84		
	21012 004W LED POWER SUPPLY MULTI-POWER WDL	1(1)
Dimtype: WDL = wireless dimmable		
Cutout dimension (mm): 84		


Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	
--	---	----------------------

DELTALIGHT

SPLITBOX 3 SPY 52 SOFT 93045

100075 9030 W




13

19810 0020

LINEAR SPREAD LENS 42

☐




13

19810 0030

SPREAD LENS 42

☐




13

19810 0040

SOFTENING LENS 42

☐




13

19810 0050

GLASS SBL 42

☐




14

19810 0060 B

HONEYCOMB 42 DOUBLE USE B

☐

Finish your product



40

19810 0100 B

SPY 52 TUBE B

☐

19810 0100 FBR

SPY 52 TUBE FBR

☐

19810 0100 FG

SPY 52 TUBE FG

☐

19810 0100 GC

SPY 52 TUBE GC

☐

19810 0100 W

SPY 52 TUBE W


☐

DELTALIGHT


SPLITBOX 3 SPY 52 SOFT 93045

100075 9030 W


Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: