
DELTALIGHT




COMPO M 92741

REFERENCE 9 15727 9230 DC

AVAILABLE IN
BLACK 9 15727 9230 B
CHROMED 9 15727 9230 C
DARK CHROMED 9 15727 9230 DC
WHITE 9 15727 9230 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 110
RECESSED DEPTH (MM)	105
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.256
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,5W / CRI>90 (R9: 60) / 2700K / 1318lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1318lm // 12,5W // 105lm/W
LED TECHNICS (LUMINAIRE)	981lm // 14,4W // 68lm/W

Requirements

LED POWER SUPPLY 700 mA - DC

Accessories

COMPO M HONEYCOMB SINGLE USE B
COMPO M LINEAR SPREAD LENS
COMPO M SPREAD LENS
COMPO M SOFTENING LENS
COMPO M GLASS SBL

For detailed installation instructions, please consult the manual : **9_15727_XXX0_HAND.pdf**

DELTALIGHT

COMPO M 92741

9 15727 9230 DC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 Plasterboard	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 Wood	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4 ☐
15710 3500	LED POWER SUPPLY MULTIPOWER 15W NO DIM 700mA	1 ☐
15710 4000	LED POWER SUPPLY MULTIPOWER 15W DIM8 700mA	1 ☐
15710 4900	LED POWER SUPPLY MULTIPOWER 20W DIM1 700mA	1 ☐
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13 ☐

Dimtype: DALI

15710 5600	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 700mA	1 ☐

Dimtype: DALI

Mounting kits



15710 0020 B MOUNTING KIT COMPO M TRIM B ☐

Cutout dimension (mm): 76

15710 0020 W MOUNTING KIT COMPO M TRIM W ☐

DELTALIGHT

COMPO M 92741

9 15727 9230 DC



15710 0050 MOUNTING KIT COMPO M TRIMLESS

Cutout dimension (mm): 76

Light altering devices

15710 1100 B COMPO M HONEYCOMB SINGLE USE B

15710 1110 COMPO M LINEAR SPREAD LENS

Cutout dimension (mm): 32,5

15710 1120 COMPO M SPREAD LENS

Cutout dimension (mm): 32,5

15710 1130 COMPO M SOFTENING LENS

Cutout dimension (mm): 32,5

15710 1140 COMPO M GLASS SBL

Cutout dimension (mm): 32,5

Notes: