



MINIGRID ON 250 92733 DIM8 B-B

100045 9228 B-B



AVAILABLE IN

BLACK-BLACK 100045 9228 B-B

BLACK-WHITE 100045 9228 B-W

WHITE-BLACK 100045 9228 W-B

WHITE-WHITE 100045 9228 W-W



[View on website](#)

General info

| | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Ceiling Surface mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 1.8 |
| ADJUSTABILITY | 0° to 20° swiveling, 350° rotatable |
| INFORMATION | 2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC |

Electrical info

| | |
|---------------------|-----------------------|
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | II |
| POWER SUPPLY | YES |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | E |

Lightsource info

| | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | 2 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm) |
| TM-30 VALUES | rf: 89 / Rg: 100 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 2082lm // 17,2W // 121lm/W |
| LED TECHNICS (LUMINAIRE) | 1695lm // 20W // 86lm/W |


For detailed installation instructions, please consult the manual: [100045_XXX8_HAND.pdf](#)

MINIGRID ON 250 92733 DIM8 B-B

100045 9228 B-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8



Notes: