

DELTALIGHT

GYN W S 927

REFERENCE 100053 9200





View on website

General info	
LOCATION	indoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 135 x 175
RECESSED DEPTH (MM)	65
THICKNESS OF MOUNTING SURFACE (MM)	min.9 - max.15
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2,2W / CRI>90 / 2700K / 242lm
LED TECHNICS (LIGHT SOURCE)	242lm // 2,2W // 110lm/W
LED TECHNICS (LUMINAIRE)	77lm // 2,5W // 31lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : **100053_XXX0_HAND.pdf**


DELTALIGHT

GYN W S 927

100053 9200

FINISH YOUR SPECIFICATION


LED power supplies	# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	**Min current | Max current**



300 90 91 LED POWER SUPPLY 350mA-DC / 15W — 6(4) ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 — 2->4 ☐

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42

Notes: