



GYN W M 930

100054 9300



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 225 x 305
RECESSED DEPTH (MM)	65
THICKNESS OF MOUNTING SURFACE (MM)	min.9 - max.15
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.8
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 8,7W / CRI>90 / 3000K / 1078lm
LED TECHNICS (LIGHT SOURCE)	1078lm // 8,7W // 124lm/W
LED TECHNICS (LUMINAIRE)	415lm // 10W // 41lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [100054_XXX0_HAND.pdf](#)

DELTALIGHT

GYN W M 930

100054 9300

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 90 91 LED POWER SUPPLY 350mA-DC / 15W

1(1)

Dimtype: non-dimmable

Cutout dimension (mm): 40



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8

1

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42

Notes: