




CAMI F20 930 DIM5

100100 9305



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK10
WEIGHT (KG)	26.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 250mA INCL.IP68 JUNCTION BOX 4P for through wiring
Electrical info	
ELECTRICAL	110-240V / 0 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 10,4W / CRI>90 (R9: 68) / 3000K / 1409lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	1409lm // 10,4W // 135lm/W
Options	
CAMI ANCHOR SET	
CBOX	

For detailed installation instructions, please consult the manual : [100100_XXX5_HAND.pdf](#)


DELTALIGHT

CAMI F20 930 DIM5

100100 9305

FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX



Cutout dimension (mm): 142 x 142

Pins and plates for bollards



31710 0030 CAMI ANCHOR SET



Notes: