


CAMI F40 930 DIM5

100101 9305



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK10
WEIGHT (KG)	49
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 700mA INCL.IP68 JUNCTION BOX 4P for through wiring

Electrical info

ELECTRICAL	110-240V / 0 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 18,1W / CRI>90 (R9: 50) / 3000K / 2859lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2859lm // 18,1W // 158lm/W

Options

CAMI ANCHOR SET
CBOX

For detailed installation instructions, please consult the manual : [100101_XXX5_HAND.pdf](#)

DELTALIGHT

CAMI F40 930 DIM5

100101 9305

FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX



Cutout dimension (mm): 142 x 142

Pins and plates for bollards



31710 0030 CAMI ANCHOR SET



Notes: