



BOXY 2 L 92733 DIM8 B-B

10727 9228 B-B

AVAILABLE IN



BLACK-BLACK 10727 9228 B-B

BLACK-FLEMISH BRONZE 10727 9228 B-FBR

BLACK-FLEMISH GOLD 10727 9228 B-FG

BLACK-GOLD MATT 10727 9228 B-MMAT

WHITE-WHITE 10727 9228 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC >> B-MMAT only interior use - other colours also exterior use

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1201lm // 13W // 90lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

BOXY 2 L 92733 DIM8 B-B

10727 9228 B-B

For detailed installation instructions, please consult the manual: [10727_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



36,3 40,4 14

300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Light altering devices



Ø40

251 70 03 01 B BOXY HONEYCOMB B

☐



Ø45 1,5

251 70 03 01 W BOXY HONEYCOMB W

☐



Ø40

251 70 03 04 B BOXY SOFTENING LENS B

☐



Ø45 1,5

251 70 03 04 W BOXY SOFTENING LENS W

☐



Ø40

251 70 03 05 B BOXY GLASS SBL B

☐



Ø45 1,5

251 70 03 05 W BOXY GLASS SBL W

☐



BOXY 2 L 92733 DIM8 B-B

10727 9228 B-B

Notes: