



## BOXY 2 L 92733 DIM8

10727 9228 W-W

AVAILABLE IN



**ALU GREY-ALU GREY** 10727 9228 A-A

**BLACK-BLACK** 10727 9228 B-B

**BLACK-FLEMISH BRONZE** 10727 9228 B-FBR

**BLACK-FLEMISH GOLD** 10727 9228 B-FG

**WHITE-WHITE** 10727 9228 W-W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.8
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	2 x REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC >> B-MMAT only interior use - other colours also exterior use

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	II
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, EAC, ENEC, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	33°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1506lm // 11,6W // 129lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1201lm // 13,3W // 90lm/W

### Accessories

BOXY HONEYCOMB  
BOXY SOFTENING LENS  
BOXY GLASS SBL

For detailed installation instructions, please consult the manual : [10727\\_XXXX\\_HAND.pdf](#)

# DELTALIGHT

## BOXY 2 L 92733 DIM8

10727 9228 W-W

### FINISH YOUR SPECIFICATION

#### Miscellaneous control equipment



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

#### Light altering devices



Ø40



1.5

Ø45

**251 70 03 01 B** BOXY HONEYCOMB B

**251 70 03 01 W** BOXY HONEYCOMB W



Ø40



1.5

Ø45

**251 70 03 04 B** BOXY SOFTENING LENS B

**251 70 03 04 W** BOXY SOFTENING LENS W



Ø40



1.5

Ø45

**251 70 03 05 B** BOXY GLASS SBL B

**251 70 03 05 W** BOXY GLASS SBL W

Notes: