

BOXY 2 L 93033 DIM8

10727 9328 W-W

AVAILABLE IN



ALU GREY-ALU GREY 10727 9328 A-A

BLACK-BLACK 10727 9328 B-B

BLACK-FLEMISH BRONZE 10727 9328 B-FBR

BLACK-FLEMISH GOLD 10727 9328 B-FG

WHITE-WHITE 10727 9328 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC >> B-MMAT only interior use - other colours also exterior use

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1574lm // 11,6W // 135lm/W
LED TECHNICS (LUMINAIRE)	1256lm // 13,3W // 94lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

For detailed installation instructions, please consult the manual : [10727_XXXX_HAND.pdf](#)

DELTALIGHT

BOXY 2 L 93033 DIM8

10727 9328 W-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Light altering devices



Ø40



Ø45

251 70 03 01 B BOXY HONEYCOMB B

251 70 03 01 W BOXY HONEYCOMB W



Ø40



Ø45

251 70 03 04 B BOXY SOFTENING LENS B

251 70 03 04 W BOXY SOFTENING LENS W



Ø40



Ø45

251 70 03 05 B BOXY GLASS SBL B

251 70 03 05 W BOXY GLASS SBL W

Notes: