





DIRO SBL S IP 83 W  
11436 8300 W

AVAILABLE IN  
**BLACK** 11436 8300 B  
**WHITE** 11436 8300 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 121
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C
CERTIFICATES	RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 5,9W / CRI>80 / 3000K / 1020lm
LED TECHNICS (LIGHT SOURCE)	1020 lm // 5 W // 173 lm/W
LED TECHNICS (LUMINAIRE)	382lm // 7W // 56lm/W

For detailed installation instructions, please consult the manual: [11436\\_XXX0\\_HAND.pdf](#)

**DIRO SBL S IP 83 W**  
 11436 8300 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 <b>System ceiling</b>	-
 <b>Plasterboard</b>	-
 <b>Stucanet</b>	-
 <b>Wood</b>	-
 <b>Stretched ceiling</b>	-

Notes: