





## DOT.COM L4 ON 92716 B-B

11525 9210 B-B

AVAILABLE IN

**BLACK-BLACK** 11525 9210 B-B

**WHITE-BLACK** 11525 9210 W-B



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	4 x REFLECTOR SP-16° INCL.LED POWER SUPPLY 1050mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	F

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 12,6W / CRI>90 (R9: 50) / 2700K / 1194lm
<b>TM-30 VALUES</b>	Rf: 92 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 60000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1194lm // 12,6W // 95lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	934lm // 14W // 64lm/W

For detailed installation instructions, please consult the manual: [11525\\_XXX0\\_HAND.pdf](#)



## DOT.COM L4 ON 92716 B-B

11525 9210 B-B

Notes: