




DOT.COM L4 ON 92732 B-B
 11525 9220 B-B

AVAILABLE IN
BLACK-BLACK 11525 9220 B-B
WHITE-BLACK 11525 9220 W-B




[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR FL-32° INCL.LED POWER SUPPLY 1050mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 12,6W / CRI>90 (R9: 50) / 2700K / 1194lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1194lm // 12,6W // 95lm/W
LED TECHNICS (LUMINAIRE)	801lm // 14W // 55lm/W

For detailed installation instructions, please consult the manual: [11525_XXX0_HAND.pdf](#)



DOT.COM L4 ON 92732 B-B

11525 9220 B-B

Notes: