DELTALIGHT®

LOGIC 40 R MOON 93015 ANO

13956 9310 ANO

AVAILABLE IN
ALU ANODIZED 13956 9310 ANO





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 43
RECESSED DEPTH (MM)	85
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR SP-15° INCL.1 x CABLE H05 RN-F 2 x 1mm² 0,5m EXCL.LED POWER SUPPLY 350mA-DC IEC 60598-2-13 : max.150kg 25N/cm² ESG 6mm

Electrical info	
CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
LED TECHNICS (LIGHT SOURCE)	385lm // 3,9W // 98lm/W
LED TECHNICS (LUMINAIRE)	85lm // 4W // 19lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT®

LOGIC 40 R MOON 93015 ANO

13956 9310 ANO

Options

LOGIC 40 BOX R
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: **13956_XXX0_HAND.pdf**

DELTALIGHT®

LOGIC 40 R MOON 93015 ANO

13956 9310 ANO

FINISH YOUR SPECIFICATION

LED power supplies			#
	**300 90 63**	LED POWER SUPPLY MULTI-POWER DIM9	1->6(6) ☐
	**300 90 68**	LED POWER SUPPLY MULTI-POWER DIM5	1->4(3) ☐
	**300 90 69**	LED POWER SUPPLY MULTI-POWER HV DIM9	3->9(9) ☐
	**300 90 124**	LED POWER SUPPLY MULTI-POWER DIM7	2->4(3) ☐
	**300 90 125**	LED POWER SUPPLY MULTI-POWER MINI DIM5	2->4(3) ☐
	**21012 0010**	LED POWER SUPPLY MULTI POWER	2->3 ☐
	**21012 0021**	LED POWER SUPPLY MULTI POWER DIM1	2->4 ☐
	**21012 0035**	LED POWER SUPPLY MULTI POWER DIM5	2->4 ☐
	**21012 005W**	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->4 ☐

DELTALIGHT®

LOGIC 40 R MOON 93015 ANO

13956 9310 ANO



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 2->2 ☐



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 3->3 ☐



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 1->3 ☐



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 1->4(3) ☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 1->3 ☐

Ground mounting boxes



13910 0010 LOGIC 40 BOX R ☐

DELTALIGHT®

LOGIC 40 R MOON 93015 ANO

13956 9310 ANO

Waterproof connection parts



216 12 00 CBOX



216 12 01 IP68 CONNECTION KIT

216 12 02 IP68 CONNECTOR 3P

Notes: