





LOGIC 40 R A 93015 INOX
13957 9310 INOX

AVAILABLE IN
INOX 13957 9310 INOX



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 43
RECESSED DEPTH (MM)	70
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR SP-15° INCL.1 x CABLE H05 RN-F 2 x 1mm² 0,5m EXCL.LED POWER SUPPLY 350mA-DC IEC 60598-2-13 : max.150kg 25N/cm² ESG 6mm
Electrical info	
CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
LED TECHNICS (LIGHT SOURCE)	385lm // 3,9W // 98lm/W
LED TECHNICS (LUMINAIRE)	186lm // 4W // 42lm/W
Requirements	
LED POWER SUPPLY 350mA-DC DIM	

LOGIC 40 R A 93015 INOX

13957 9310 INOX

Options

LOGIC 40 BOX R

CBOX

IP68 CONNECTION KIT










IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [13957_XXX0_HAND.pdf](#)

LOGIC 40 R A 93015 INOX


13957 9310 INOX

FINISH YOUR SPECIFICATION

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->6(6)	<input type="checkbox"/>
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->4(3)	<input type="checkbox"/>
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	3->9(9)	<input type="checkbox"/>
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	2->4(3)	<input type="checkbox"/>
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2->4(3)	<input type="checkbox"/>
	21012 0010 LED POWER SUPPLY MULTI POWER	2->3	<input type="checkbox"/>
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	2->4	<input type="checkbox"/>
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	2->4	<input type="checkbox"/>
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->4	<input type="checkbox"/>


LOGIC 40 R A 93015 INOX

13957 9310 INOX




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1->3



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1->4(3)




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1->3



Ground mounting boxes



13910 0010 LOGIC 40 BOX R








DELTA LIGHT®

LOGIC 40 R A 93015 INOX

13957 9310 INOX

Waterproof connection parts

	216 12 00 CBOX	<input type="checkbox"/>
	216 12 01 IP68 CONNECTION KIT	<input type="checkbox"/>
	216 12 02 IP68 CONNECTOR 3P	<input type="checkbox"/>

Notes: