



## LOGIC 40 R A 93015

13957 9310 INOX

AVAILABLE IN  
**INOX** 13957 9310 INOX



 [View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 43
<b>RECESSED DEPTH (MM)</b>	70
<b>INGRESS PROTECTION</b>	IP67
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK08
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR SP-15° INCL.1 x CABLE H05 RN-F 2 x 1mm <sup>2</sup> 0,5m EXCL.LED POWER SUPPLY 350mA-DC IEC 60598-2-13 : max.150kg 25N/cm <sup>2</sup> ESG 6mm

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm
<b>TM-30 VALUES</b>	rf: 92 / Rg: 98
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG2 (threshold 0,6m)
<b>LM80</b>	L90B10 > 41000
<b>BEAMANGLE</b>	15°
<b>LED TECHNICS (LIGHT SOURCE)</b>	385lm // 3,9W // 98lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	186lm // 4,5W // 42lm/W

### Requirements

LED POWER SUPPLY 350mA-DC DIM

### Options

LOGIC 40 BOX R  
CBOX  
IP68 CONNECTION KIT  
IP68 CONNECTOR 3P

# DELTALIGHT

## LOGIC 40 R A 93015

13957 9310 INOX

For detailed installation instructions, please consult the manual : [13957\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

3

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

6(6)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2->4(3)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72

# DELTALIGHT

## LOGIC 40 R A 93015

13957 9310 INOX




**300 90 67**

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3

**Dimtype: 1-10V or DALI or push button**




**300 90 68**

LED POWER SUPPLY MULTI-POWER DIM5

4(3)

**Dimtype: DALI**

**Cutout dimension (mm): 72**




**300 90 69**

LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 124**

LED POWER SUPPLY MULTI-POWER DIM7

2->4(3)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125**

LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3)

**Dimtype: DALI**

**Cutout dimension (mm): 55**




**300 90 135**

LED POWER SUPPLY MULTI-POWER HV

5->7

**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**




**21012 0010**

LED POWER SUPPLY MULTI POWER

2->3

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021**

LED POWER SUPPLY MULTI POWER DIM1

4

**Dimtype: 1-10V**

**Cutout dimension (mm): 54**




**21012 0035**

LED POWER SUPPLY MULTI POWER DIM5

4

**Dimtype: DALI**

**Cutout dimension (mm): 54**



**21012 004W**

LED POWER SUPPLY MULTI-POWER WDL

6(6)


**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**

# DELTALIGHT

## LOGIC 40 R A 93015

13957 9310 INOX




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

4

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)

Dimtype: non-dimmable

Cutout dimension (mm): 60




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 30


### Ground mounting boxes



**13910 0010** LOGIC 40 BOX R

Cutout dimension (mm): 140

### Waterproof connection parts



**216 12 00** CBOX


Cutout dimension (mm): 142 x 142

# DELTALIGHT

## LOGIC 40 R A 93015

13957 9310 INOX

---



**216 12 01** IP68 CONNECTION KIT



**216 12 02** IP68 CONNECTOR 3P



Notes: