



LOGIC 40 R A MOON 93015

13958 9310 INOX

AVAILABLE IN
INOX 13958 9310 INOX



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 43
RECESSED DEPTH (MM)	70
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR SP-15° INCL.1 x CABLE H05 RN-F 2 x 1mm ² 0,5m EXCL.LED POWER SUPPLY 350mA-DC IEC 60598-2-13 : max.150kg 25N/cm ² ESG 6mm

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm
TM-30 VALUES	rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	385lm // 3,9W // 98lm/W
LED TECHNICS (LUMINAIRE)	85lm // 4,5W // 19lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Options

LOGIC 40 BOX R
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

DELTALIGHT

LOGIC 40 R A MOON 93015

13958 9310 INOX

For detailed installation instructions, please consult the manual : [13958_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

3

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

3

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

3

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




300 90 61 LED POWER SUPPLY MULTI-POWER DIM6

3

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

6(6)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

2->4(3)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72

DELTALIGHT

LOGIC 40 R A MOON 93015

13958 9310 INOX




300 90 67

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

3



Dimtype: 1-10V or DALI or push button



300 90 68


LED POWER SUPPLY MULTI-POWER DIM5

4(3)



Dimtype: DALI

Cutout dimension (mm): 72



300 90 69


LED POWER SUPPLY MULTI-POWER HV DIM9

2->9(10)



Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 84



300 90 124


LED POWER SUPPLY MULTI-POWER DIM7

2->4(3)



Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125


LED POWER SUPPLY MULTI-POWER MINI DIM5

4(3)



Dimtype: DALI

Cutout dimension (mm): 55



300 90 135


LED POWER SUPPLY MULTI-POWER HV

5->7



Dimtype: non-dimmable

Cutout dimension (mm): 90



21012 0010


LED POWER SUPPLY MULTI POWER

2->3



Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021


LED POWER SUPPLY MULTI POWER DIM1

4



Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035


LED POWER SUPPLY MULTI POWER DIM5

4



Dimtype: DALI

Cutout dimension (mm): 54



21012 004W

LED POWER SUPPLY MULTI-POWER WDL

6(6)




Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84

DELTALIGHT

LOGIC 40 R A MOON 93015

13958 9310 INOX




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

4

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 50




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

4(3)

Dimtype: non-dimmable

Cutout dimension (mm): 60




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3

Dimtype: DALI

Cutout dimension (mm): 30


Ground mounting boxes



13910 0010 LOGIC 40 BOX R

Cutout dimension (mm): 140

Waterproof connection parts




216 12 00 CBOX

Cutout dimension (mm): 142 x 142

DELTALIGHT

LOGIC 40 R A MOON 93015

13958 9310 INOX



216 12 01 IP68 CONNECTION KIT



216 12 02 IP68 CONNECTOR 3P



Notes: