



OBLIX S 15 930 N

15112 9300 N

AVAILABLE IN
FLEMISH BRONZE OUTDOOR 15112 9300 FBRX
ANTHRACITE (DARK GREY) 15112 9300 N



 [View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	557lm // 7W // 84lm/W

Options

PIN 17
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [15112_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00

CBOX

☐



216 12 01

IP68 CONNECTION KIT

☐




216 12 02

IP68 CONNECTOR 3P

☐

Pins and plates for bollards



15222 0170

PIN T7

☐

Notes: