



QOBY X R 92733 DIM8

19122 9238 W

AVAILABLE IN
BLACK 19122 9238 B
WHITE 19122 9238 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	864lm // 9,9W // 87lm/W

For detailed installation instructions, please consult the manual : [19122_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

QOBY X R 92733 DIM8

19122 9238 W