





## QOBY X R 93033 DIM8 B

19122 9338 B

AVAILABLE IN

**BLACK** 19122 9338 B

**WHITE** 19122 9338 W



[View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP44
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1089lm // 8,6W // 127lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	903lm // 10W // 91lm/W

For detailed installation instructions, please consult the manual: [19122\\_XXX8\\_HAND.pdf](#)



## QOBY X R 93033 DIM8 B

19122 9338 B

Notes: