





QOBY X R 93033 DIM8

19122 9338 W

AVAILABLE IN
BLACK 19122 9338 B
WHITE 19122 9338 W



 [View on website](#)



| General info | |
|------------------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Ceiling Surface mounted |
| INGRESS PROTECTION | IP44 |
| WEIGHT (KG) | 0.6 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC |
| Electrical info | |
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | D |
| Lightsource info | |
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| TM-30 VALUES | rf: 90 / Rg: 99 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| BEAMANGLE | 33° |
| LED TECHNICS (LIGHT SOURCE) | 1089lm // 8,6W // 127lm/W |
| LED TECHNICS (LUMINAIRE) | 903lm // 9,9W // 91lm/W |

For detailed installation instructions, please consult the manual : [19122_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

QOBY X R 93033 DIM8

19122 9338 W