





SPY S 92733 DIM8 B

19876 9228 B

AVAILABLE IN
BLACK 19876 9228 B
WHITE 19876 9228 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	535lm // 10W // 54lm/W

Requirements	
SPY TUBE	

Accessories	
HONEYCOMB 50	
LINEAR SPREAD LENS 50	
SPREAD LENS 50	
SOFTENING LENS 50	
GLASS SBL 50	



SPY S 92733 DIM8 B

19876 9228 B


For detailed installation instructions, please consult the manual: [**19876_XXXX_HAND.pdf**](#)

SPY S 92733 DIM8 B

19876 9228 B

FINISH YOUR SPECIFICATION


Control gear, ballast and transformers




300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Light altering devices




413 03 01 B HONEYCOMB 50 B

☐


413 03 02 LINEAR SPREAD LENS 50

☐

413 03 03 SPREAD LENS 50

☐


413 03 04 SOFTENING LENS 50

☐

413 03 05 GLASS SBL 50

☐

Finish your product

 <div>53</div> <div>Ø60</div>	<u>414 01 00 B</u>	SPY TUBE B	<input type="checkbox"/>
	<u>414 01 00 FBR</u>	SPY TUBE FBR	<input type="checkbox"/>
	<u>414 01 00 FG</u>	SPY TUBE FG	<input type="checkbox"/>
	<u>414 01 00 MMAT</u>	SPY TUBE MMAT	<input type="checkbox"/>
	<u>414 01 00 SG</u>	SPY TUBE SG	<input type="checkbox"/>
	<u>414 01 00 W</u>	SPY TUBE W	<input type="checkbox"/>

Notes: