





SPY S 92733 DIM8 W

19876 9228 W

AVAILABLE IN
BLACK 19876 9228 B
WHITE 19876 9228 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	535lm // 10W // 54lm/W

Requirements

SPY TUBE

Accessories

HONEYCOMB 50
LINEAR SPREAD LENS 50
SPREAD LENS 50
SOFTENING LENS 50
GLASS SBL 50



SPY S 92733 DIM8 W

19876 9228 W


For detailed installation instructions, please consult the manual: [**19876_XXXX_HAND.pdf**](#)

SPY S 92733 DIM8 W

19876 9228 W

FINISH YOUR SPECIFICATION


Control gear, ballast and transformers




300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Light altering devices




413 03 01 B HONEYCOMB 50 B

☐


413 03 02 LINEAR SPREAD LENS 50

☐

413 03 03 SPREAD LENS 50

☐

413 03 04 SOFTENING LENS 50

☐

413 03 05 GLASS SBL 50


☐

DELTA LIGHT®

SPY S 92733 DIM8 W

19876 9228 W

Finish your product

	<div><div>414 01 00 B</div><div>SPY TUBE B</div></div>	<input type="checkbox"/>
	<div><div>414 01 00 FBR</div><div>SPY TUBE FBR</div></div>	<input type="checkbox"/>
	<div><div>414 01 00 FG</div><div>SPY TUBE FG</div></div>	<input type="checkbox"/>
	<div><div>414 01 00 MMAT</div><div>SPY TUBE MMAT</div></div>	<input type="checkbox"/>
	<div><div>414 01 00 SG</div><div>SPY TUBE SG</div></div>	<input type="checkbox"/>
	<div><div>414 01 00 W</div><div>SPY TUBE W</div></div>	<input type="checkbox"/>

Notes: