


SPYCO ON AC 92733 DIM8

19919 9228 B

AVAILABLE IN
BLACK 19919 9228 B
WHITE 19919 9228 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-33° BLACK version: INCL.SPY TUBE S B / WHITE version: INCL.SPY TUBE S W

Electrical info

ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm
TM-30 VALUES	rf: 92 / Rg: 98
SDCM	SDCM3
RISKGROUPE	RG1
LM80	L80B10 > 67000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	597lm // 8W // 75lm/W
LED TECHNICS (LUMINAIRE)	452lm // 8W // 57lm/W

Accessories

SPY TUBE S

For detailed installation instructions, please consult the manual : [19919_XXX8_HAND.pdf](#)


DELTALIGHT

SPYCO ON AC 92733 DIM8

19919 9228 B

FINISH YOUR SPECIFICATION

Finish your product



414 02 00 B

SPY TUBE S B

414 02 00 FBR

SPY TUBE S FBR

414 02 00 FG

SPY TUBE S FG

414 02 00 MMAT

SPY TUBE S MMAT

414 02 00 SG

SPY TUBE S SG

414 02 00 W

SPY TUBE S W

Notes: