



**SPYCO ON AC 92733 DIM8 B**  
19919 9228 B

AVAILABLE IN  
**BLACK** 19919 9228 B  
**WHITE** 19919 9228 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 350° rotatable
INFORMATION	REFLECTOR FL-33° BLACK version: INCL.SPY TUBE S B / WHITE version: INCL.SPY TUBE S W

Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80B10 > 67000
LED TECHNICS (LIGHT SOURCE)	597lm // 8W // 75lm/W
LED TECHNICS (LUMINAIRE)	452lm // 8W // 57lm/W

Accessories	
SPY TUBE S	


For detailed installation instructions, please consult the manual: [19919\\_XXX8\\_HAND.pdf](#)

SPYCO ON AC 92733 DIM8 B

19919 9228 B

FINISH YOUR SPECIFICATION

Finish your product



**414 02 00 B**

SPY TUBE S B

☐

**414 02 00 MMAT**

SPY TUBE S MMAT

☐

**414 02 00 W**

SPY TUBE S W

☐

Notes: